

RESULTS & STANDARDS

SPORTS FLOORING	STANDARD	THICKNESS	RESULTS	SQ/FT PER ROLL
Width		ALL	5' 10" (1.8 m)	
Active 50 ⁽¹⁾		5mm	65' 7" (20 m)	387.50 (36.0 m ²)
Active Pro ⁽²⁾		7mm	85' 3" (26 m) ⁽²⁾	503.75 (46.8 m ²)
American Sports Flooring Standard ⁽⁵⁾	ASTM F2772	ALL	Meets all Requirements	
European Sports Flooring Standard ⁽⁵⁾	EN 14904	ALL	Class 1	
Vertical Deformation	ASTM F2157 / ASTM F2772	ALL	PASS	
Ball Rebound >90%	ASTM F2117 / ASTM F2772	ALL	99%	
Active 50 - Force Reduction	ASTM F2569 / ASTM F2772/ EN 14808	5mm	Class 2	
Active Pro - Force Reduction	ASTM F2569 / ASTM F2772 / EN14808	7mm	Class 2	
Surface Finish Effect (Slide) 80 -110	ASTM E303/ ASTM F2772/ EN 13036	ALL	PASS	
Wear Layer	ASTM F1303 / ASTM F410	ALL	Type 1 / Grade 1	
Fire Rating	ASTM E648	ALL	Class 1	
Resistance to Chemicals	ASTM F925	ALL	Excellent	
Static Load 175 psi	ASTM F970	ALL	PASS	
Phthalate Free ⁽³⁾	ASTM F3414-20	ALL	YES	
Abrasion Resistance	EN ISO 5470-1	ALL	0.095mm PASS	
Rolling Load ≥ 1500 N	EN 1569	ALL	0.05mm PASS	
Impact Resistance	EN 1517	ALL	PASS	
Color Fastness	EN ISO 105-B02	ALL	Excellent	
Indoor Air Quality (IAQ) ⁽⁴⁾	California Section 01350	ALL	Certified by FloorScore®	
ISO 9001:2015		YES	Certificate No.: IN32750A	
ISO 14001:2015		YES	Certificate No.: IN31472B	
Heavy Metals		ALL	NO	

(1) Superior embossed surface will not trap dirt, while giving the perfect coefficient of friction for athletic sporting activities. (2) 85 foot rolls allow for no cross seams on main basketball court. (3) Active is a phthalate-free flooring. The phthalate-free plasticizers selected by Icon are approved for food containers and can be used for toys intended to be placed in the mouth by children. (4) Our products contribute to better indoor air quality and are FloorScore® Certified; certified by SCS Global. (5) Active vinyl flooring has been designed for strength and performance and is approved in both the United States and Europe by ASTM F2772 and EN14904.