

Specification

SPC FLOORING for heavy commercial use
 PUR Polyurethane Reinforcement
 Product Standard ASTM F3261-17



ISO 9001
 ISO 14001
 ISO 18001

CERTIFICATION & CLASSIFICATION

TYPE OF FLOOR COVERING	RESILIENT FLOORING IN MODULAR FORMAT WITH RIGID CORE (SPC)
CE CERTIFICATION	Yes
CLASSIFICATION	Heavy Traffic : Class 33

TECHNICAL CHARACTERISTICS

TOTAL THICKNESS	6.50 MM
WEAR LAYER THICKNESS	20 mil WL 0.50 MM
SURFACE TREATMENT	PUR
TOTAL WEIGHT	2.17 LBS / SQFT = 10.40 kg/m ²
WEAR LAYER BINDER CONTENT	TYPE I
FORM OF DELIVERY	9" X 60" = 18.75 sq.ft 5 Pieces per box

TECHNICAL PERFORMANCES

DIMENSIONAL STABILITY	≤ 0.10%
REACTION TO FIRE	Bfl- S1 PASS
RESIDUAL INDENTATION	Required Value : ≤ 0.10mm Average Measured Value : 0.03mm
FURNITURE LEG	No Damage
CASTOR CHAIR	No Damage
CURL RESULTANT TO HEAT	≤ 2mm PASS
SMOKE RESISTANCE	PASS
IMPACT SOUND REDUCTION	w = 11 Db
LIGHT FASTNESS	PASS
RESISTANCE TO CHEMICALS	Good Resistance PASS
SLIP RESISTANCE	R9 PASS
STATIC LOAD	PASS